

# Package: adbcsqlite (via r-universe)

July 9, 2024

**Title** 'Arrow' Database Connectivity ('ADBC') 'SQLite' Driver

**Version** 0.13.0.9000

**Description** Provides a developer-facing interface to the 'Arrow' Database Connectivity ('ADBC') 'SQLite' driver for the purposes of building high-level database interfaces for users. 'ADBC' <<https://arrow.apache.org/adbc/>> is an API standard for database access libraries that uses 'Arrow' for result sets and query parameters.

**License** Apache License (>= 2)

**Encoding** UTF-8

**Roxxygen** list(markdown = TRUE)

**RoxxygenNote** 7.2.3

**SystemRequirements** SQLite3

**Suggests** nanoarrow, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Config/build/bootstrap** TRUE

**URL** <https://github.com/apache/arrow-adbc>,  
<https://arrow.apache.org/adbc/current/r/adbcsqlite/>

**BugReports** <https://github.com/apache/arrow-adbc/issues>

**Imports** abcdrivermanager

**Repository** https://apache.r-universe.dev

**RemoteUrl** https://github.com/apache/arrow-adbc

**RemoteRef** HEAD

**RemoteSha** 66ecd33dceb9b8f9fe513abf99685e21929a7064

## Contents

adbcsqlite . . . . .	2
----------------------	---

<b>Index</b>	4
--------------	---

---

adbcsqlite	<i>ADBC SQLite3 Driver</i>
------------	----------------------------

---

## Description

ADBC SQLite3 Driver

## Usage

```
adbcsqlite()

## S3 method for class 'adbcsqlite_driver_sqlite'
adbc_database_init(driver, ..., uri = ":memory:")

## S3 method for class 'adbcsqlite_database'
adbc_connection_init(database, ..., adbc.connection.autocommit = NULL)

## S3 method for class 'adbcsqlite_connection'
adbc_statement_init(
  connection,
  ...,
  adbc.ingest.target_table = NULL,
  adbc.ingest.mode = NULL,
  adbc.sqlite.query.batch_rows = NULL
)
```

## Arguments

driver	An <a href="#">adbc_driver()</a> .
...	Driver-specific options. For the default method, these are named values that are converted to strings.
uri	A URI to a database path or ":memory:" for an in-memory database.
database	An <a href="#">adbc_database</a> .
adbc.connection.autocommit	Use FALSE to disable the default autocommit behaviour.
connection	An <a href="#">adbc_connection</a>
adbc.ingest.target_table	The name of the target table for a bulk insert.
adbc.ingest.mode	Whether to create (the default) or append.
adbc.sqlite.query.batch_rows	The number of rows per batch to return.

## Value

An [adbcdrivermanager::adbc\\_driver\(\)](#)

**Examples**

`adbcsqlite()`

# Index

adbc\_connection, [2](#)  
adbc\_connection\_init.adbcsqlite\_database  
    (adbcsqlite), [2](#)  
adbc\_database, [2](#)  
adbc\_database\_init.adbcsqlite\_driver\_sqlite  
    (adbcsqlite), [2](#)  
adbc\_driver(), [2](#)  
adbc\_statement\_init.adbcsqlite\_connection  
    (adbcsqlite), [2](#)  
adbcdrivermanager::adbc\_driver(), [2](#)  
adbcsqlite, [2](#)